

IMPRESS

SENSORS & SYSTEMS

Unit 6B, Mercury House, Calleva Park
Aldermaston, Berkshire, RG7 8PN

Tel: +44 (0)118 981 7980

Fax: +44 (0)118 981 7990

e-mail: info@impress-sensors.co.uk

Website: www.impress-sensors.co.uk

Pressure - Temperature - Level - Flow - Analytical - Control - Indication - Data logging



ASM 400 ASM 405

Display and Switching Units

- ▶ for 4 ... 20 mA / 2-wire or 0 ... 10 V / 3-wire signals
- ▶ easy mounting in fixing hole \varnothing 20.5 mm
- ▶ electrical connection via cords
- ▶ **ASM 400:** digit height 7 mm, external diameter 46 mm
- ▶ **ASM 405:** digit height 10 mm, external diameter 49.5 mm

Description

Our display and switching units are intended to equip different devices with a digital display on the easiest way. Additionally, the option is given to offer up to 2 PNP open collector contacts for a limiting value control.

Operation

Configuration of the display and switching units ASM 400 and ASM 405 is menu-driven via two miniature push buttons, located in the front. Following parameters could be configured: decimal point, zero point, end point, damping, measuring value update, switch-on and switch-off points, hysteresis- or compare mode as well as switch-on and switch-off delay of the contacts. Those parameters are being stored in an EEPROM and, thus, are being kept also in case of power breakdown. Limit exceeding in both directions can be displayed as a message. Furthermore an access protection is provided.

Applications

- ▶ manufacturing of transmitter
- ▶ mechanical engineering
- ▶ process control

- ▶ rugged, rotatable plastic housing
- ▶ easy configuration via two push buttons
- ▶ 4-digit, red LED display, digit height 7 mm or 10 mm
- ▶ up to two configurable contacts
- ▶ ASM 400: optionally with Ex-protection for 4 ... 20 mA / 2-wire
- ▶ ASM 405: optionally with component Ex- approval for 4 ... 20 mA / 2-wire

Characteristics



ASM 400 / ASM 405
Display and Switching Units

Visit the website: www.impress-sensors.co.uk

ASM 400 / ASM 405

Display and Switching Units

Technical Data

Analogue signal											
2-wire-system	4 ... 20 mA	Ex-protection: 4 ... 20 mA									
3-wire-system	0 ... 10 V										
Supply											
2-wire-system	supplied by current loop; voltage drop $\leq 6\text{ V}$; $V_S = (V_{T\min} \dots V_{T\max}) + 6 V_{DC}$ with V_T = supply of the used transmitter Ex-protection: max. $28 V_{DC}$ (for combination of transmitter and ASM 400 / ASM 405)										
3-wire-system	display is supplied parallel with the transmitter; $V_{S\min} = 8 V_{DC} \dots V_{T\min}$; $V_{S\max} = V_{T\max} \dots 36 V_{DC}$ with V_T = supply of the used transmitter										
Contact (optional)											
Number, type	1 or 2 independent PNP open collector contacts										
Switching performance	$V_{Switch} = V_S - 2\text{ V}$; contact rating max. 125 mA, short-circuit resistant										
Repeatability	$\leq \pm 0.1\%$ FSO										
Switching frequency	max. 10 Hz										
Switching cycles	$> 100 \times 10^6$										
Delay time	0 ... 100 sec.										
Electrical protection											
Short-circuit protection	permanent										
Reverse polarity protection	no damage, but also no function										
Ingress protection	unmounted: IP 00; mounted: front sided up to IP 65 (ASM 400) or IP 60 (ASM 405); ingress protection of the total appliance depends on the customer's housing										
Miscellaneous											
Display	4-digit, 7-segment LED display, digit height 7 mm (ASM 400) or 10 mm (ASM 405), range of indication -1999 ... +9999; accuracy $0.1\% \pm 1$ digit; digital damping 0.3 ... 30 sec. (programmable); measured value update 0.0 ... 10 sec. (programmable)										
Permissible temperatures	electronics / environment: -25 ... 80 °C	storage: -40 ... 85 °C									
Material of display housing	PA 6.6, polycarbonate										
Explosion protection (optionally for 4 ... 20 mA / 2-wire)											
Ex-designation	ASM 400: zone (0) 1: II (1) 2 G EEx ia IIC T4 (AX11-ASM 400) ASM 405: zone 0: II 1 G EEx ia IIC T4 (component approval ASM 405)										
Safety technical maximum values	$U_i = 28\text{ V}$, $\Sigma I_i = 93\text{ mA}$, $\Sigma P_i = 660\text{ mW}$; max. switching current 1 : 70 mA, max. $L_o = 2\text{ mH}$; max. $C_o = 40\text{ nF}$										
Permissible temperature	environment: -25 ... 70° C										
	¹ the real switching current in the application depends on the power supply unit										
Wirings diagrams											
<p>2-wire-system (current)</p>		<p>3-wire-system (voltage)</p>									
Dimensions											
<table border="1"> <thead> <tr> <th></th> <th>ASM 400</th> <th>ASM 405</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>46</td> <td>49.5</td> </tr> <tr> <td>B</td> <td>19.5</td> <td>18</td> </tr> </tbody> </table>				ASM 400	ASM 405	A	46	49.5	B	19.5	18
	ASM 400	ASM 405									
A	46	49.5									
B	19.5	18									
Pin configuration											
electrical connection via cords (length 150 mm)	cord colours (DIN 47100)										
	2-wire-system	3-wire-system									
Supply +	white	white									
Supply -	brown	brown									
Contact 1	green	green									
Contact 2	yellow	yellow									
Signal input +	-	red									
Signal input -	-	brown									

This data sheet contains product specification; properties are not guaranteed. Subject to change without notice.

Visit the website: www.impress-sensors.co.uk