

# DT85 Series 2

## Data Logger

### Intelligent Data Logging Products

- USB memory for easy data & program transfer
- Dual Channel Isolation Technology
- 2 Serial 'Smart Sensor' ports
- User Definable allocation of memory size & mode
- Web Interface
- FTP for automatic data transfer
- Modbus for SCADA connection
- SDI-12 (multiple networks)
- Up to 48 Analog ( $\pm 30V$ ) sensor inputs
- Expandable to 800 analog inputs
- 12 Flexible Digital channels



Specifications

### The Smarter Solution

The *dataTaker DT85* is a smart data logger that provides an extensive array of features that allow it to be used across a wide variety of applications. The *DT85* is a robust, stand alone, low power data logger featuring USB memory stick support, 18 bit resolution, extensive communications capabilities and built-in display. The *dataTaker DT85*'s Dual Channel concept allows up to 32 isolated or 48 common referenced analog inputs to be used in many combinations.

With support for multiple SDI-12 sensor networks, Modbus for SCADA systems, FTP and Web interface, 12V regulated output to power sensors, the *DT85* is ready to be rolled out into environmental, industrial and many other types of monitoring projects.

### Versatile Measurement

Analog and digital channels, high-speed counter inputs, phase encoder inputs and programmable serial sensor channels allow the *DT85* to easily connect to most sensors and data measurement sources. Temperature, voltage, current, 4-20mA loops, resistance, bridges, strain gauges, frequency, digital, serial and calculated measurements can all be scaled, logged and returned in engineering units or within statistical reporting. Group sampling, logging, alarm and control tasks within schedules to suit your requirements. Smart sensors, GPS, PLCs and other intelligent devices are supported via 2 serial sensor ports (RS232 or RS422/485), with our optional *CANgate* interface available for CAN bus applications.

Manage a variety of sensors or devices using the Sensor Power options via dedicated power output, digital outputs or the latching relay configurations.

### Superior Data Storage and Communications

Store up to 5 million data points in user defined memory, log as much or as little as you need with independent control of schedule size and mode. Overwrite or stop logging once allocated memory is full. Archive data on alarm event, copy to USB memory or transfer via FTP, the choice is yours.

Communications features include RS232 with modem support, USB, Ethernet and USB memory stick ports. Connect to the *DT85* locally, remotely or over the Internet. The web interface allows users to configure the *DT85*, access logged data and see current measurements as mimics or in a list using a web browser. FTP provides data to your office over the internet or mobile phone network, without the need for polling or specific host software.

Take the next step and experience the *DT85* by contacting your local distributor or *dataTaker* office.

### Applications include:

- Research & Development
- Agricultural Research
- Weather Stations
- Total Energy Monitoring
- Environmental Monitoring
- Temperature Profiling
- Thermistor Arrays
- Aquaculture
- Structural Monitoring
- Strain Gauges
- Process Monitoring
- Fault Identification
- Machine Down Time
- Pressure
- Load Cells
- Flow
- Vehicle Testing
- GPS
- *CANgate* (optional)
  - CAN bus
  - J1939
  - OBDII

**FREE**  
Software &  
Technical  
Support

**IMPRESS**  
SENSORS & SYSTEMS

Unit 6B, Mercury House, Calleva Park  
Aldermaston, Berkshire, RG7 8PN  
Tel: +44 (0)118 981 7980  
Fax: +44 (0)118 981 7990  
e-mail: [info@impress-sensors.co.uk](mailto:info@impress-sensors.co.uk)  
Website: [www.impress-sensors.co.uk](http://www.impress-sensors.co.uk)

## Analog Channels

16 analog input channels (expandable to 300\*)

Each channel is independent and supports: one isolated 3-wire or 4-wire input, or two isolated 2-wire inputs, or three common referenced 2-wire inputs.

The following maximums apply.

Two wire with common reference terminal:

48 (expandable to 800\*)

Two wire isolated: 32 (expandable to 600\*)

Three and four wire isolated: 16 (expandable to 300\*)

\*Expansion requires optional CEM20

## Fundamental Input Ranges

The fundamental inputs that the DT85 can measure are voltage, current, resistance and frequency. All other measurements are derived from these.

Full Scale	Resolution	Full Scale	Resolution
±30 mVdc	0.25 µV	100 Ω	1.5 mΩ
±300 mVdc	2.5 µV	1000 Ω	15 mΩ
±3 Vdc	25 µV	10,000 Ω	150.00 mΩ
±30 Vdc	250 µV	100 Hz	0.0002 %
±0.3 mA	2.5 nA	10 kHz	0.0002 %
±3 mA	25 nA		
±30 mA	250 nA		

Auto-ranging is supported over 3 ranges.

## Accuracy

Measurement at ...	5°C to 40°C	-45°C to 70°C
DC Voltage	0.1%	0.35%
DC Current	0.15%	0.45%
DC Resistance	0.1%	0.35%
Frequency	0.1%	0.25%

Accuracy table above is % of reading ±0.01% of full scale.

## Sampling

Integrates over 50/60Hz line period for accuracy and noise rejection

Maximum sample speed: 25Hz

Effective resolution: 18 bits

Linearity: 0.01%

Common mode rejection: >90dB

Line series mode rejection: >35dB

## Inputs

Inter-Channel Isolation: 100V (relay switching)

Analog Section Isolation: 100V (opto-isolated)

Input impedance: 100KΩ, >100MΩ

Common mode range: ±3.5V or ±35V on 30V range

## Sensor Excitation (Supply)

Analog channels: selectable 250µA or 2.5mA precision current source, 4.5V voltage source, or switched external supply.

General Purpose: Switchable 12V regulated supply for powering sensors & accessories. (max 150mA)

## Analog Sensors

Supports a wide range of sensors including, but not limited to, those listed below. A wide range of sensor scaling and linearising facilities including polynomials, expressions and functions.

## Thermocouples

Types: B, C, D, E, G, J, K, N, R, S, T

Calibration standard: ITS-90

## RTDs

Materials supported: Pt, Ni, Cu

Resistance range: 10Ω to 10KΩ

## Thermistors

Types: YSI 400xx Series, other types\*

Resistance range: <10kΩ\*\*

\* Other thermistor types are supported by thermistor scaling and calculated channels.

\*\*Resistance range can be increased with the use of a parallel resistor.

## Monolithic Temperature Sensors

Types supported: LM34 - 60, AD590, 592, TMPxx  
LM135, 235, 335

## Strain Gauge and Bridge Sensors

Configurations: ¼, ½ & full bridge

Excitation: voltage or current

## 4-20mA Current Loop

Internal 100R shunt or external shunt resistor

## Digital Channels

### Digital Input/Outputs

8 bi-directional channels

Input Type: 8 logic level (max 20/30V)

Output Type: 4 with open drain FET

(max: 30V, 100mA), 4 with logic output.

### Relay Output

1 latching relay, contacts (max: 30Vdc, 1A)

## Counter Channels

### Low Speed Counters

8 counters shared with digital inputs.

Low speed counters do not function in sleep mode.

Size: 32 bit

Max Count rate: 10 Hz

### Dedicated Counter Inputs

4 high speed or 2 phase encoder (quadrature) inputs

Size: 32 bit

Max Count rate: 10 kHz

Input type: 2 logic level inputs (max ±30V), 2 sensitive inputs (10mV) for magnetic pick-ups (max ±10V)

## Serial Channels

### SDI-12

4 SDI-12 inputs, shared with digital channels. Each input can support multiple SDI-12 sensors.

### Generic Serial Sensor

Flexible options to allow data to be logged from a wide range of smart sensors and data streams.

Available ports: Serial Sensor Port (RS232, RS422, RS485) or Host RS232 Port\*

Baud rate: 300 to 115200

\*If used as a Serial Sensor channel then the Host Port is not available for other communications.

## Calculated Channels

Combine values from analog, digital and serial sensors using expressions involving variables and functions.

Functions: An extensive range of Arithmetic, Trigonometric, Relational, Logical and Statistical functions are available.

## Alarms

Condition: high, low, within range and outside range

Delay: optional time period for alarm response

Actions: set digital outputs, transmit message, execute any dataTaker command.

## Scheduling of Data Acquisition

Number of schedules: 11

Schedule rates: 10ms to days

## Data Storage

### Internal Store

Capacity: 64MB = approx 5,000,000 data points

Removable USB store device (optional accessory)

Types: compatible with USB 1.1 or USB 2.0 drives, e.g. Flash drive.

Capacity: approx. 90,000 data points per megabyte.

## Communication Interfaces

### Ethernet Port

Interface: 10BaseT (10Mbps)

Protocol: TCP/IP

### USB Port

Interface: USB 1.1 (virtual COM port)

Protocol: ASCII command

### Host RS232 Port

Speed: 300 to 115200 baud (57,600 default)

Flow Control: Hardware (RTS/CTS),

Software (XON/XOFF), None

Handshake lines: DCD, DSR, DTR, RTS, CTS

Modem support: auto-answer and dial out

Protocols: ASCII Command, TCP/IP (PPP),

Modbus, Serial Sensor

## Serial Sensor Port

Interface: RS232, RS422m RS485

Speed: 300 to 57,600 baud

Flow Control: Hardware (RTS/CTS),

Software (XON/XOFF), None

Protocols: Modbus, Serial Sensor

## Network (TCP/IP) Services

Uses Ethernet and/or Host RS232 (PPP) ports

## Command Interface

Access the ASCII command interface of the DT85 via TCP/IP

## Web Server

Access current data and status from any web browser. Custom pages can be defined. Download data in CSV format. Command interface window. Define mimic displays.

## Modbus Server (slave)

Access current data and status from any Modbus client (e.g. SCADA system)

## FTP Server

Access logged data from any FTP client or web browser

## FTP Client

Automatically upload logged data direct to an FTP server

## System

### Display and Keypad

Type: LCD, 2 line by 16 characters, backlight.

Display Functions: channel data, alarms, system status.

Keypad: 6 keys for scrolling and function execution.

Status LEDs: 4 for sample, disk, attention and power.

## Firmware Upgrade

Via: RS232, Ethernet, USB or USB disk.

## Real Time Clock

Normal resolution: 200µs

Accuracy: ±1 min/year (0°C to 40°C),

±4 min/year (-40°C to 70°C)

## Power Supply

External voltage range: 10 to 30Vdc

Internal battery: 6Vdc 4Ahr lead acid

Peak Power: 12W (12Vdc 1A)

## Average power Consumption

Using 12Vdc external power source

Sampling Speed	Average Power
1 second	1350 mW
5 second	500 mW
30 second	135 mW
5 minutes	70 mW
1 hour	60 mW

## Typical Operating Time

from internal 6Vdc, 4Ahr battery

Sampling Speed	Operating Time
1 second	1 day
5 second	3 days
1 minute	1 month
1 hour	9.5 months

## Physical and Environment

Construction: Powder coated zinc and anodized aluminum.

Dimensions: 300 x 137 x 65mm

Weight: 2.5kg (5kg shipping)

Temperature range: -45°C to 70°C \*

Humidity: 85% RH, non-condensing

\*reduced battery life and LCD operation outside range -15°C to 50°C

## Accessories Included

Resource CD: includes software, video training and user manual.

Comms cable: USB cable

Line adaptor: 110/240Vac to 15Vdc, 800mA

## Optional Accessories

A range of accessories are available. Contact your local distributor or visit [www.datataker.com](http://www.datataker.com)



Pressure - Temperature - Level - Flow - Analytical - Control - Indication - Data logging

Unit 6B, Mercury House, Calleva Park

Aldermaston, Berkshire, RG7 8PN

Tel: +44 (0)118 981 7980

Fax: +44 (0)118 981 7990

e-mail: [info@impress-sensors.co.uk](mailto:info@impress-sensors.co.uk)

Website: [www.impress-sensors.co.uk](http://www.impress-sensors.co.uk)